
SYNTHETIC ROPE



Stud Socket Fitting for Extruded Jacket Kevlar Rope



Electroline synthetic rope fittings for Kevlar ropes with extruded jackets excel in meeting the need for a quick, reliable end termination. The fittings perform on polyurethane, Nylon II, and Hytrel jacket materials for ropes with the following construction: standard wire rope, contra-helical, parallel, and electro-mechanical. This fitting features a clevis (fork/jaw) connection and a swageless rope termination, allowing it to be quickly installed in the field without special tools.

- Available for rope 3/16 to 3/4" in size.
- Machined from aluminum to provide lightweight strength.

Specifications

Rope Material Kevlar Rope

Jacket Material Hytrel, Nylon II, Polyurethane

Jacket TypeExtrudedMaterialAluminum

Connector Type Stud

Termination Type Swageless

Available Products

Rope Size (In)	Part No.	Thread	Dim A	Dim C	Dim D
3/16	KA-318	1/2-13	4-3/4	8-3/8	15/16
1/4	KA-325	5/8-11	4-3/4	9-3/8	1
5/16	KA-331	3/4-10	5	10-7/8	1-1/8
3/8	KA-337	3/4-10	5-1/8	11-7/8	1-1/4
7/16	KA-343	7/8-9	6	15	1-1/2
1/2	KA-350	1-8	6-3/4	16-1/8	1-3/4
9/16	KA-356	1-1/8-7	7-1/8	17-1/2	2
5/8	KA-362	1-1/4-7	7-1/8	18-7/8	2-1/8
3/4	KA-375	1-1/2-6	8	21	2-1/2

PDF generated on 2025-09-16 at 18:41 by <u>electrolineusa.com</u>. Information is provided for reference only. Please contact Electroline at <u>info@electrolineusa.com</u> or 1-800-321-0870 to confirm specifications or discuss customization options.