



A 3D model of a mechanical part, likely a drill bit or a similar tool. The part is shown in a perspective view. It has a cylindrical body with a threaded section at the top. The body is divided into several sections. The dimensions are labeled as follows: A is the diameter of the top section; B is the length of the top section; C is the diameter of the middle section; D is the length of the middle section; E is the diameter of the bottom section; F is the length of the bottom section; G is the diameter of the tip section; H is the length of the tip section; I is the diameter of the base section; J is the length of the base section; K is the diameter of the handle section; L is the length of the handle section; M is the diameter of the grip section; N is the length of the grip section; O is the diameter of the base section; P is the length of the base section; Q is the diameter of the tip section; R is the length of the tip section; S is the diameter of the base section; T is the length of the base section; U is the diameter of the handle section; V is the length of the handle section; W is the diameter of the grip section; X is the length of the grip section; Y is the diameter of the base section; Z is the length of the base section.

- Swageless rope termination allows the swivel to be field-installed without expensive tools or complicated processes.
- Made from alloy steel and zinc-plated for corrosion resistance.
- Ultimate strength exceeds the rated Safe Working Load (SWL).

Material	Zinc Plated Steel
Termination Type	Swageless
Connector Type	Clevis
Water Pressure Resistance	Moderate

Rope Size (In)	Part No.	SWL Pounds (3:1)	SWL Pounds (5:1)	Dim A	Dim C - Pin Dia.	Dim D	Dim F	Dim I	Dim L	Overall Length
1/8	3412	1666	1000	7/8	1/4	1/4	1/2	7/16	-	3-15/16
3/16	3418	2066	1240	1	5/16	5/16	5/8	1/2	-	4-9/16
1/4	3425	2500	1500	1-1/8	3/8	3/8	3/4	9/16	-	5-3/16
5/16	3431	5000	3000	1-7/8	3/4	13/16	1-3/8	1	2	7-7/16
3/8	3437	6666	4000	1-7/8	3/4	13/16	1-3/8	1	2	7-15/16
7/16	3443	10000	6000	2-3/8	3/4	1	1-3/8	1-1/8	2-1/4	9-1/2
1/2	3450	10000	6000	2-3/8	3/4	1	1-3/8	1-1/8	2-1/4	9-1/2
9/16	3456	16666	10000	3-1/4	1	1-1/8	1-3/4	1-1/4	3	11-11/16
5/8	3462	16666	10000	3-1/4	1	1-1/8	1-3/4	1-1/4	3	11-11/16
3/4	3475	28333	17000	3-5/8	1-1/8	1-9/16	2-1/8	1-1/2	3-1/4	13-5/8
7/8	3487	33333	20000	3-3/4	1-1/4	1-3/4	3-1/8	1-7/8	3-1/2	16-1/2
1	3499	50000	30000	4-1/8	1-3/8	1-3/4	3-1/8	1-7/8	4	17-15/16