



- The tapered design helps prevent snagging on other equipment or cables.
- Ultimate strength exceeds the rated Safe Working Load (SWL).
- Built with high-strength alloy steel and zinc-plated for corrosion resistance.

Specifications

Material	Zinc Plated Alloy Steel
Termination Type	Eye
Connector Type	Hook
Water Pressure Resistance	Moderate

Available Products

Part No.	SWL Pounds (3:1)	SWL Pounds (5:1)	Dim A	Dim E	Dim G	Dim H	Dim J - Hole Dia.	Dim K	Length to Inside of Hook
6112	2300	1380	7/8	1/4	7/8	3/8	1/4	3/8	5-3/8
6125	5000	3000	1-1/4	5/16	31/32	1/2	3/8	7/16	7-1/16
6137	8000	4800	1-1/2	1/2	1	23/32	5/8	5/8	7-7/8
6150	11500	6900	1-7/8	3/4	1-11/32	15/16	7/8	15/16	10-13/16
6162	18500	11100	2-7/16	1	1-11/16	1-5/16	1-1/4	1-3/16	15-1/4
6175	31500	18900	2-7/8	1-1/4	2-1/4	1-5/8	1-3/8	1-1/2	18-7/8
6181	31500	18900	2-7/8	1-1/4	2-1/4	1-5/8	1-3/8	1-1/2	18-7/8
6187	33333	20000	3-5/8	1-23/32	3	2-27/32	1-5/8	1-13/16	24-15/16
6199	50000	30000	3-5/8	2	3	2-25/32	2	2-1/8	25-11/16
61125	83333	50000	4-1/2	2-1/8	4	2-7/8	2-1/4	2-3/8	33-13/16
61150	116667	70000	5-3/8	2-1/4	4-1/4	3-1/8	2-1/4	2-3/8	39-5/8