



A technical drawing of a metal hook, likely a lifting hook, with various dimensions labeled. The hook has a threaded top section, a central body with a hole, and a U-shaped base. Dimensions are indicated by arrows and letters: A is the height of the base flange, B is the height of the central body, C is the total height, D is the width of the base, E is the width of the central body, and F is the width of the base flange.

- Available for ropes from 7/16 to 1 inches in size.
- Fitting strength exceeds the rated breaking strength of most ropes.
- Forge from solid steel; galvanized or zinc-plated options are available for increased corrosion resistance.

Termination Type	Swageless
Connector Type	Clevis

Rope Size (In)	Galvanized Steel	Self-Colored Steel	Dim A	Dim B	Dim C	Dim D	Dim E	Dim F	EIPS Breaking Strength (lbs)
7/16	PD-143-X	PD-143-N	1-1/16	2	7-3/16	2-19/32	1	1	20400
1/2	PD-150-X	PD-150-N	1-1/16	2	7-3/16	2-19/32	1	1	26600
9/16	PD-156-X	PD-156-N	1-1/4	2-1/2	8-5/8	3-11/64	1-1/4	1-3/16	33600
5/8	PD-162-X	PD-162-N	1-1/4	2-1/2	8-5/8	3-11/64	1-1/4	1-3/16	41200
3/4	PD-175-X	PD-175-N	1-7/16	3	10-3/16	3-11/16	1-1/2	1-3/8	58800
7/8	PD-187-X	PD-187-N	1-15/16	2-7/8	12-11/16	4-7/8	1-7/8	1-1/2	79600
1	PD-199-X	PD-199-N	2-3/16	3-5/16	17	5-5/8	1-7/8	1-7/8	103400