



- Angular contact bearings support higher rotational speeds and longer rope lengths.
- Tapered ends are designed to prevent snags on other equipment or cables.
- Ultimate strength exceeds the rated Safe Working Load (SWL).

Material	Stainless Steel
Termination Type	Clevis
Connector Type	Clevis
Water Pressure Resistance	High

Part No.	SWL Pounds (5:1)	SWL Pounds (3:1)	Dim A	Dim C - Pin Dia.	Dim D	Dim F	Dim I	Overall Length
SSP-6725	900	1500	1-1/4	3/8	19/32	11/16	7/16	5
SSP-6737	1800	3000	1-1/2	7/16	19/32	13/16	9/16	5-5/8
SSP-6750	3600	6000	1-7/8	5/8	3/4	15/16	13/16	7-3/4
SSP-6762	6000	10000	2-7/16	7/8	1	1-9/16	1-1/8	11-3/8
SSP-6775	9600	16000	3-1/4	1-1/8	1-9/16	2-1/8	1-1/4	13-7/16
SSP-6787	12000	20000	3-5/8	1-1/2	1-3/4	3-1/2	1-3/4	17-1/2
SSP-6799	16800	28000	3-5/8	1-1/2	1-3/4	3-1/2	1-3/4	18-7/8