




[Forged Series] Open Body Double Socket Turnbuckle



Electrolines's open-body swageless turnbuckle features a dual rope termination socket, allowing it to be quickly installed and tensioned in the field without special tools or processes.

- Available for ropes from 1/4 to 1-1/2 inches in diameter. Breaking strength exceeds that of most ropes.
- Fitting strength exceeds the rated breaking strength of most ropes.
- Made from forged steel, a galvanized option is available for increased corrosion resistance.
- Three different takeup length options are available for each rope size.

Specifications

Material	Galvanized Steel
Termination Type	Swageless
Connector Type	Swageless

Available Products

Rope Size (In.)	Dimensions (In.)		Takeup	IPS Breaking Strength (lbs.)
	C - Min.	D		
1/4	14-9/16	1	6	5880
1/4	17-9/16	1	9	5880
1/4	20-9/16	1	12	5880
5/16	15-3/8	1	6	9160
5/16	18-3/8	1	9	9160
5/16	21-3/8	1	12	9160
3/8	19-3/4	1-1/8	6	13120
3/8	19-3/4	1-1/8	9	13120
3/8	22-3/4	1-1/8	12	13120
7/16	17-3/4	1-1/2	6	17780
7/16	20-3/4	1-1/2	9	17780
7/16	23-3/4	1-1/2	12	17780
1/2	19-1/4	1-1/2	6	23000
1/2	22-1/4	1-1/2	9	23000
1/2	25-1/4	1-1/2	12	23000
9/16	27-7/8	1-13/16	12	29000

Rope Size (In.)	Dimensions (In.)		Takeup	IPS Breaking Strength (lbs.)
	C - Min.	D		
9/16	33-7/8	1-13/16	18	29000
5/8	27-7/8	1-3/4	12	35800
5/8	33-7/8	1-3/4	18	35800
3/4	33-3/8	2-5/8	12	51200
3/4	39-3/8	2-5/8	18	51200
3/4	45-3/8	2-5/8	24	51200
7/8	33-7/8	2-5/8	12	69200
7/8	39-7/8	2-5/8	18	69200
7/8	45-3/8	2-5/8	24	69200
1	37-1/2	3	12	89800
1	43-1/2	3	18	89800
1	49-1/2	3	24	89800
1-1/8	51-7/8	3	18	113000
1-1/8	57-7/8	3	24	113000
1-1/4	51-7/8	3-1/2	18	138800
1-1/4	57-7/8	3-1/2	24	138800
1-3/8	66-5/8	4	24	167000
1-1/2	66-5/8	4	24	197800

PDF generated on 2025-10-08 at 15:17 by electrolineusa.com. Information is provided for reference only. Please contact Electroline at info@electrolineusa.com or 1-800-321-0870 to confirm specifications or discuss customization options.