
QUICK CONNECT. STRONG SUPPORT.

EYE



[Forged Series] Oval Eye Swivel Socket Fitting (Non-roller Bearing)



Electroline's oval eye swivel fitting includes a non-roller bearing swivel, making it easy to position the fitting when connecting. The swageless rope termination allows the fitting to be quickly installed in the field without special tools or processes.

- Available for ropes from 7/16 to 1-3/8 inches in diameter.
- Fitting strength exceeds the rated breaking strength of most ropes.
- Made from forged steel; a galvanized option is available for increased corrosion resistance.

Specifications

Termination Type Swageless **Connector Type** Eye

Available Products

Rope Size (In)	Self-Colored Steel	Zinc Plated Steel	Dim A	Dim B	Dim C	Dim D	Dim E	Dim F	IPS Breaking Strength(l bs)
7/16	Y-1143-N	Y-1143-V	10-9/32	1-5/8	1-3/16	2-3/4	3	1-7/16	17780
1/2	Y-1150-N	Y-1150-V	10-9/32	1-5/8	1-3/16	2-3/4	3	1-7/16	23000
9/16	Y-1156-N	Y-1156-V	11-1/8	1-5/8	1-3/16	2-3/4	3	1-7/8	29000
5/8	Y-1162-N	Y-1162-V	11-1/8	1-5/8	1-3/16	2-5/8	3	1-7/8	35800
3/4	Y-1175-N	Y-1175-V	12-1/2	1-7/8	1-3/4	3-1/4	3-5/8	2-3/16	51200
7/8	Y-1187-N	Y-1187-V	13-1/2	1-7/8	1-3/4	3-1/4	3-5/8	2-5/8	69200
1	Y-1199-N	Y-1199-V	15-7/16	2-1/8	1-3/4	3-3/8	4	2-7/8	83800
1-1/8	Y-11112-N	Y-11112-V	20-1/16	2-5/8	2-1/4	4-5/16	4-7/8	3-3/4	113000
1-1/4	Y-11125-N	Y-11125-V	21-1/2	2-5/8	2-1/4	4-5/16	4-7/8	4-1/16	138800
1-3/8	Y-11137-N	Y-11137-V	27-1/16	4	3	4-1/2	7	4-3/8	167000

PDF generated on 2025-09-17 at 13:47 by electrolineusa.com. Information is provided for reference only. Please contact Electroline at info@electrolineusa.com or 1-800-321-0870 to confirm specifications or discuss customization options.