
QUICK CONNECT. STRONG SUPPORT.

FITTINGS



Swivel Hook Socket Fitting (Non-Roller Bearing)



Electroline swagless swivel hook fitting features a non-roller bearing swivel that allows the hook to be easily positioned when attaching. The swageless rope termination enables the hook to be quickly installed in the field without special tools or processes.

- For both wire and synthetic rope from 3/16 to 1 inch in size.
- Fitting strength exceeds the rated breaking strength of most ropes.
- Available in both zinc-plated and self-colored steel.

Specifications

Termination Type Swageless **Connector Type** Hook

Available Products

<pre>IPS Breaking Strength(lbs)</pre>	Dim E	Dim D	Dim C	Dim A	Zinc Plated Steel	Self-Colored Steel	Rope Size (In)
3340	1	2-7/8	3/4	6-19/32	Y-2518-V	Y-2518-N	3/16
5880	1-1/16	3-3/16	15/16	7-7/16	Y-2525-V	Y-2525-N	1/4
9160	1-1/8	3-5/8	15/16	8-1/4	Y-2531-V	Y-2531-N	5/16
13120	1-1/4	4-3/32	1-1/8	9-5/16	Y-2537-V	Y-2537-N	3/8
17780	1-1/4	4-3/32	1-1/4	10-5/8	Y-2543-V	Y-2543-N	7/16
23000	1-1/2	4-15/16	1-7/16	11-13/16	Y-2550-V	Y-2550-N	1/2
29000	1-7/8	6-1/2	1-9/16	13-11/16	Y-2556-V	Y-2556-N	9/16
35800	1-7/8	6-1/2	1-3/4	14-3/4	Y-2562-V	Y-2562-N	5/8
51200	2-1/4	7-9/16	2	17-1/4	Y-2575-V	Y-2575-N	3/4
69200	2-1/2	8-11/16	2-1/8	19-7/16	Y-2587-V	Y-2587-N	7/8
89800	3-3/8	11	2-1/2	21-15/16	Y-2599-V	Y-2599-N	1

PDF generated on 2025-09-17 at 13:46 by <u>electrolineusa.com</u>. Information is provided for reference only. Please contact Electroline at <u>info@electrolineusa.com</u> or 1-800-321-0870 to confirm specifications or discuss customization options.