
SYNTHETIC ROPE



## Stud Socket Fitting for Braided Jacket Kevlar Rope



Electroline synthetic rope fittings for Kevlar rope with braided jackets excel in meeting the need for a quick, reliable end termination. These fittings use a swagless design with an internal taper pin that allows them to be installed in the field without special tools or complicated processes. They are selected for both the rope size and rated rope strength. This fitting features a threaded stud that can be used to connect and tension the rope to a fixed point.

- Available for rope 3/16 to 3/4" in size.
- Machined from aluminum to provide lightweight strength.

## **Specifications**

Rope MaterialKevlar RopeJacket TypeBraidedMaterialAluminumConnector TypeStudTermination TypeSwageless

## **Available Products**

Dim D	Dim C	Dim A	Rated Breaking Strength	Part No.	Rope Size (In)
1	7-5/16	3	2400 to 4400	IKA-318	3/16
1-1/8	10	4-3/4	4400 to 6000	IKA-325	1/4
1-3/8	11	5-1/8	6000 to 9000	IKA-331	5/16
1-1/2	12	5-1/8	9000 to 13000	IKA-337	3/8
2	16	7-1/8	16000 to 22000	IKA-350	1/2
2	17	7-1/8	28000 to 37000	IKA-362	5/8
3	21-3/4	10	35000 to 63000	IKA-375	3/4

**PDF generated on 2025-04-19 at 14:17 by** <u>electrolineusa.com</u>. Information is provided for reference only. Please contact Electroline at <u>info@electrolineusa.com</u> or 1-800-321-0870 to confirm specifications or discuss customization options.