



A diagram of a hook and shackle assembly. The shackle is at the top, with a threaded pin. Two horizontal arrows, labeled 'A', point towards the shackle from the left and right. Below the shackle is a hook. A diagonal line passes through the hook, and two arrows, labeled 'G', point towards each other along this line, representing a compressive force.

- Swageless rope termination allows the swivel to be field-installed without expensive tools or complicated processes.
- Made from alloy steel and zinc-plated for corrosion resistance.
- Ultimate strength exceeds the rated Safe Working Load (SWL).

Termination Type	Swageless
Connector Type	Hook
Material	Zinc Plated Steel

Rope Size (In)	Part No.	SWL Pounds (3:1)	SWL Pounds (5:1)	Dim A	Dim G	Length to Inside of Hook
5/16	3031	5000	3000	1-7/8	1	7
3/8	3037	6666	4000	1-7/8	1-1/16	7-7/8
7/16	3043	10000	6000	2-1/4	1-11/32	10-3/16
1/2	3050	10000	6000	2-1/4	1-11/32	10-3/16
9/16	3056	16666	10000	3	1-11/16	12-5/8
5/8	3062	16666	10000	3	1-11/16	12-5/8
3/4	3075	28333	17000	3-1/4	2-1/16	14-5/8
7/8	3087	33333	20000	3-1/2	2-1/4	16-11/16
1	3099	50000	30000	4	3	18-5/8