



A diagram of a hook joint. It shows a vertical shaft with a hook at the bottom. The shaft has a central section with a yellow band. Dimension A is indicated by a horizontal double-headed arrow across the central section. Dimension Q is indicated by a diagonal double-headed arrow from the center of the shaft to the top of the hook.

- Swageless rope termination allows the swivel to be field-installed without expensive tools or complicated processes.
- Ultimate strength exceeds the rated Safe Working Load (SWL).
- Built with high-strength alloy steel and zinc-plated for corrosion resistance.

Material	Zinc Plated Alloy Steel
Termination Type	Swageless
Connector Type	Hook
Water Pressure Resistance	Moderate

Rope Size (In)	Part No.	SWL Pounds (3:1)	SWL Pounds (5:1)	Dim A	Dim G	Length to Inside of Hook	Overall Length
1/8	6012	2300	1380	7/8	7/8	5-5/16	5-5/16
1/4	6025	5000	3000	1-1/4	31/32	8-5/16	8-5/16
3/8	6037	8000	4800	1-1/2	1	9-1/2	9-1/2
1/2	6050	11500	6900	1-7/8	1-11/32	12-15/16	12-15/16
5/8	6062	18500	11100	2-7/16	1-11/16	17-9/16	17-9/16
3/4	6075	31500	18900	2-7/8	2-1/4	21-1/8	21-1/8
3/4	6081	31500	18900	2-7/8	2-1/4	21-1/8	21-1/8
7/8	6087	33333	20000	3-5/8	3	25-15/16	25-15/16
1	6099	50000	30000	3-5/8	3	27-13/16	27-13/16
1-1/4	60125	83333	50000	4-1/2	4	40-9/16	40-9/16
1-1/2	60150	116667	70000	5-3/8	4-1/4	48-1/8	48-1/8