




## Open Body Clevis and Socket Turnbuckle



Electrolines's open-body clevis (fork/jaw) and socket turnbuckle features a swageless rope termination, allowing it to be quickly installed and tensioned in the field without special tools or processes.

- Available for ropes from 1/4 to 1-1/2 inches in diameter. Breaking strength exceeds that of most ropes.
- Fitting strength exceeds the rated breaking strength of most ropes.
- Made from forged steel, a galvanized option is available for increased corrosion resistance.
- Three different takeup length options are available for each rope size.

### Specifications

|                         |                  |
|-------------------------|------------------|
| <b>Material</b>         | Galvanized Steel |
| <b>Termination Type</b> | Swageless        |
| <b>Connector Type</b>   | Clevis           |

### Available Products

| Rope Size (In) | Part No.   | IPS Breaking Strength | Takeup | Dim A  | Dim B   | Dim C - Min. | Dim D | Dim E | Dim F |
|----------------|------------|-----------------------|--------|--------|---------|--------------|-------|-------|-------|
| 1/4            | XD-4025-AX | 5880                  | 6      | 9/16   | 1-1/4   | 14-3/8       | 1     | 5/8   | 7/16  |
| 1/4            | XD-4025-BX | 5880                  | 9      | 9/16   | 1-1/4   | 17-3/8       | 1     | 5/8   | 7/16  |
| 1/4            | XD-4025-CX | 5880                  | 12     | 9/16   | 1-1/4   | 20-3/8       | 1     | 5/8   | 7/16  |
| 5/16           | XD-4031-AX | 9160                  | 6      | 9/16   | 1-1/4   | 14-11/16     | 1     | 5/8   | 7/16  |
| 5/16           | XD-4031-BX | 9160                  | 9      | 9/16   | 1-1/4   | 17-11/16     | 1     | 5/8   | 7/16  |
| 5/16           | XD-4031-CX | 9160                  | 12     | 9/16   | 1-1/4   | 20-11/16     | 1     | 5/8   | 7/16  |
| 3/8            | XD-4037-AX | 13120                 | 6      | 25/32  | 1-9/16  | 16           | 1-1/8 | 3/4   | 1/2   |
| 3/8            | XD-4037-BX | 13120                 | 9      | 25/32  | 1-9/16  | 19           | 1-1/8 | 3/4   | 1/2   |
| 3/8            | XD-4037-CX | 13120                 | 12     | 25/32  | 1-9/16  | 22           | 1-1/8 | 3/4   | 1/2   |
| 7/16           | XD-4043-AX | 17780                 | 6      | 31/32  | 1-13/16 | 17-5/16      | 1-1/2 | 15/16 | 5/8   |
| 7/16           | XD-4043-BX | 17780                 | 9      | 31/32  | 1-13/16 | 20-5/16      | 1-1/2 | 15/16 | 5/8   |
| 7/16           | XD-4043-CX | 17780                 | 12     | 31/32  | 1-13/16 | 23-5/16      | 1-1/2 | 15/16 | 5/8   |
| 1/2            | XD-4050-AX | 23000                 | 6      | 31/32  | 1-13/16 | 18           | 1-1/2 | 15/16 | 5/8   |
| 1/2            | XD-4050-BX | 23000                 | 9      | 31/32  | 1-13/16 | 21           | 1-1/2 | 15/16 | 5/8   |
| 1/2            | XD-4050-CX | 23000                 | 12     | 31/32  | 1-13/16 | 24           | 1-1/2 | 15/16 | 5/8   |
| 9/16           | XD-4056-CX | 29000                 | 12     | 1-3/32 | 2-1/8   | 25-1/2       | 1-3/4 | 1-1/8 | 3/4   |
| 9/16           | XD-4056-DX | 29000                 | 18     | 1-3/32 | 2-1/8   | 31-1/2       | 1-3/4 | 1-1/8 | 3/4   |
| 5/8            | XD-4062-CX | 35800                 | 12     | 1-3/32 | 2-1/8   | 25-1/2       | 1-3/4 | 1-1/8 | 3/4   |

| Rope Size (In) | Part No.    | IPS Breaking Strength | Takeup | Dim A   | Dim B  | Dim C - Min. | Dim D | Dim E  | Dim F |
|----------------|-------------|-----------------------|--------|---------|--------|--------------|-------|--------|-------|
| 5/8            | XD-4062-DX  | 35800                 | 18     | 1-3/32  | 2-1/8  | 31-1/2       | 1-3/4 | 1-1/8  | 3/4   |
| 3/4            | XD-4075-CX  | 51200                 | 12     | 1-17/32 | 3-3/8  | 33-7/16      | 2-5/8 | 1-3/4  | 1-1/8 |
| 3/4            | XD-4075-DX  | 51200                 | 18     | 1-17/32 | 3-3/8  | 39-7/16      | 2-5/8 | 1-3/4  | 1-1/8 |
| 3/4            | XD-4075-EX  | 51200                 | 24     | 1-17/32 | 3-3/8  | 45-7/16      | 2-5/8 | 1-3/4  | 1-1/8 |
| 7/8            | XD-4087-CX  | 69200                 | 12     | 1-17/32 | 3-3/8  | 33-7/16      | 2-5/8 | 1-3/4  | 1-1/8 |
| 7/8            | XD-4087-DX  | 69200                 | 18     | 1-17/32 | 3-3/8  | 39-7/16      | 2-5/8 | 1-3/4  | 1-1/8 |
| 7/8            | XD-4087-EX  | 69200                 | 24     | 1-17/32 | 3-3/8  | 45-7/16      | 2-5/8 | 1-3/4  | 1-1/8 |
| 1              | XD-4099-CX  | 89800                 | 12     | 1-25/32 | 3-1/2  | 36-1/2       | 3     | 2-1/16 | 1-3/8 |
| 1              | XD-4099-DX  | 89800                 | 18     | 1-25/32 | 3-1/2  | 42-1/2       | 3     | 2-1/16 | 1-3/8 |
| 1              | XD-4099-EX  | 89800                 | 24     | 1-25/32 | 3-1/2  | 48-1/2       | 3     | 2-1/16 | 1-3/8 |
| 1-1/8          | XD-40112-DX | 113000                | 18     | 2-1/16  | 4-3/16 | 48-1/16      | 3     | 2-3/8  | 1-5/8 |
| 1-1/8          | XD-40112-EX | 113000                | 24     | 2-1/16  | 4-3/16 | 54-1/16      | 3     | 2-3/8  | 1-5/8 |
| 1-1/4          | XD-40125-DX | 138800                | 18     | 2-1/16  | 4-3/16 | 48-1/16      | 3-1/2 | 2-3/8  | 1-5/8 |
| 1-1/4          | XD-40125-EX | 138800                | 24     | 2-1/16  | 4-3/16 | 54-1/16      | 3-1/2 | 2-3/8  | 1-5/8 |
| 1-3/8          | XD-40137-EX | 167000                | 24     | 2-17/32 | 4-5/16 | 60-5/16      | 4     | 2-1/2  | 2     |
| 1-1/2          | XD-40150-EX | 197800                | 24     | 2-17/32 | 4-5/16 | 60-5/16      | 4     | 2-1/2  | 2     |

PDF generated on 2025-04-16 at 17:44 by [electrolineusa.com](https://electrolineusa.com). Information is provided for reference only. Please contact Electroline at [info@electrolineusa.com](mailto:info@electrolineusa.com) or 1-800-321-0870 to confirm specifications or discuss customization options.