



Technical drawing of a hook wrench (Gabelschlüssel) showing dimensions A, B, C, D, and E. The drawing includes a side view of the tool and a cross-sectional view of the hexagonal head. Dimension A is the total length, B is the length of the handle, C is the width of the head, D is the width of the hook, and E is the radius of the hook's curve.

- For both wire and synthetic rope from 3/16 to 1 inch in size.
- Fitting strength exceeds the rated breaking strength of most ropes.
- Available in both zinc-plated and self-colored steel.

Termination Type	Swageless
Connector Type	Hook

Rope Size (In)	Self-Colored Steel	Zinc Plated Steel	IPS Breaking Strength	Dim A	Dim C	Dim D	Dim E
3/16	Y-2518-N	Y-2518-V	3340	6-19/32	3/4	2-7/8	1
1/4	Y-2525-N	Y-2525-V	5880	7-7/16	15/16	3-3/16	1-1/16
5/16	Y-2531-N	Y-2531-V	9160	8-1/4	15/16	3-5/8	1-1/8
3/8	Y-2537-N	Y-2537-V	13120	9-5/16	1-1/8	4-3/32	1-1/4
7/16	Y-2543-N	Y-2543-V	17780	10-5/8	1-1/4	4-3/32	1-1/4
1/2	Y-2550-N	Y-2550-V	23000	11-13/16	1-7/16	4-15/16	1-1/2
9/16	Y-2556-N	Y-2556-V	29000	13-11/16	1-9/16	6-1/2	1-7/8
5/8	Y-2562-N	Y-2562-V	35800	14-3/4	1-3/4	6-1/2	1-7/8
3/4	Y-2575-N	Y-2575-V	51200	17-1/4	2	7-9/16	2-1/4
7/8	Y-2587-N	Y-2587-V	69200	19-7/16	2-1/8	8-11/16	2-1/2
1	Y-2599-N	Y-2599-V	89800	21-15/16	2-1/2	11	3-3/8