
QUICK CONNECT. STRONG SUPPORT.

HOOK (SWIVEL AND NON-SWIVEL)



Non-Swivel Hook Socket Fitting



Electroline's non-swivel hook fitting features a swageless rope termination, allowing it to be quickly installed in the field without special tools or processes.

- For both wire and synthetic rope from 3/16 to 1 inch in size.
- Fitting strength exceeds the rated breaking strength of most ropes.
- Made from solid steel, a zinc-plated option is available for increased corrosion resistance.

Specifications

Termination Type Swageless **Connector Type** Hook

Available Products

Rope Size (In)	Self-Colored Steel	Zinc Plated Steel	IPS Breaking Strength	Dim A	Dim C	Dim D	Dim E
3/16	Y-2618-N	Y-2618-V	3340	5-5/16	3/4	2-7/8	
1/4	Y-2625-N	Y-2625-V	5880	5-7/8	15/16	3-3/16	1-1/16
5/16	Y-2631-N	Y-2631-V	9160	6-21/32	15/16	3-5/8	1-1/8
3/8	Y-2637-N	Y-2637-V	13120	7-19/32	1-1/8	4-3/32	1-1/4
7/16	Y-2643-N	Y-2643-V	17780	8-5/16	1-1/4	4-3/32	1-1/4
1/2	Y-2650-N	Y-2650-V	23000	9-23/32	1-7/16	4-15/16	1-1/2
9/16	Y-2656-N	Y-2656-V	29000	12	1-9/16	6-1/2	1-7/8
5/8	Y-2662-N	Y-2662-V	35800	12	1-3/4	6-1/2	1-7/8
3/4	Y-2675-N	Y-2675-V	51200	14-1/2	2	7-9/16	2-1/4
7/8	Y-2687-N	Y-2687-V	69200	16-15/32	2-1/8	8-11/16	2-1/2
1	Y-2699-N	Y-2699-V	89800	19-3/16	2-1/2	11	3-3/8

PDF generated on 2025-04-16 at 17:44 by electrolineusa.com. Information is provided for reference only. Please contact Electroline at info@electrolineusa.com or 1-800-321-0870 to confirm specifications or discuss customization options.